

Paper or poly band business cards, postcards and brochures with the SP Bander. Banding your work is easy and more economical than boxing or shrink wrapping. The SP Bander comes as a standard tabletop model, with an available optional high capacity stand.

FEATURES

- Available in either paper or poly rolls
- Adjustable backstops for feeding ease
- LCD readout for operation adjustments
- Adjustable lag time for variable feeding
- Adjustable tension for delicate jobs
- Optional Jumbo roll stand available for high volume users
- Closed arch system for feeding ease and durability
- Quick release to cut and eject the banding in case of misfeeds
- Manual, Foot-pedal, or automatic sensor-driven operation



SPECIFICATIONS

Minimum Input Size	1.2" x 0.4" (3cm x 1cm)
Maximum Input Size	18" x 7.9" (46cm x 20cm)
Banding Specifications	1.2" (3cm) wide x 100-120 microns (thickness)
Banding Types	Poly film or paper
Banding Roll Size	150 metre (492') length
Banding Speed	20 pieces/minute (operator dependent)
Sealing Method	Thermal sealing (self-welding tape)
Feeding Method	Manual
Tabletop/Floor	Tabletop model (optional stand available shown above)
Controls	Manual, foot pedal, automatic
Machine Weight	Without Stand: 90lbs (41kg) With Stand: 140lbs (63.5kg)
Machine Dimensions	Without Stand: 25"x15"x 20" (63.5cm x 38.1cm x 50.8cm) With Stand: 25"x 15"x50" (63.5cm x 38.1cm x 127cm)
Electrical	110-130V, 60Hz, 15A

NOTE: Machine performance will vary based on stock weight, type, and specifications of the job being performed.
WARRANTY: 1 year warranty (excludes consumables)