

DRY-LAM®
Preserve and protect what matters.

FUJiPLA

High-Speed, Commercial-Grade, Fujipla Laminator!


The newest, commercial-grade Fujipla laminator by Dry-Lam has everything you know and love about the previous ALM line for automatic feeding, laminating, trimming, and stacking sheets, but is now faster and better with improved features and functionality! Laminating up to 68" per minute, it is 25% faster than the ALM3230.

Automatic Laminator

Item #: 04DLHLA2301




New & Improved!



Simple-slide paper size adjustment



Improved film roll installation



Upgraded multi-thickness feed tray



Easy-to-use Color Screen & Controls

Recommended Film*

- | | |
|------------------|---------------|
| • DL-HLA38GLOSS | 1.5 mil Gloss |
| • DL-HLA75GLOSS | 3.0 mil Gloss |
| • DL-HLA75MATT | 3.0 mil Matte |
| • DL-HLA125GLOSS | 5.0 mil Gloss |

*Additional options available. Contact sales for more info



FEATURES

- **Zero waste** mode for reduced film scraps on border-cut sheets
- **Joint mode** with gap or no gap, for folded applications or multi-sheet prints
- **Ultra-quick warm-up** time of less than 5 minutes
- Automatic **single or double-sided** lamination
- 2 Automatic trim options
 - Flush-cut: precise, micro-adjustable with ± 3 mm margin adjust
 - Border-cut: custom-sealed options with 4-sided trim uniformity
- Hands-free, **automatic feed** tray
- Includes **stand with waste basket** to collect scraps
- Simple operation with **specially encoded film** for auto settings

NEW “EVERSTICK” FILM ROLLS

- **New and improved** HLA film designed for optimal operation of the HLA-2301*
- **Strong adhesion** with no peeling or bubbling, even on flush-cut sheets
- Proprietary **chip-reading** design
- **Automatically sets** to the correct temperature for the film in use

*Former ALM SAP film rolls are not compatible with the HLA-2301

SPECIFICATIONS	
Model	HLA-2301
Laminating Width	12.6"
Speed	68" per minute
Film Thickness	1.5 - 10 mil film (10 mil single-side only)
Paper Thickness	17lb - 100lb cover
Laminating Thickness	16 mil
Heat Type	Heated Rollers
Temperature Range	170 - 270°F
Warm-up Time	Less than 5 minutes
Paper Sizes	8.5"x5.5", 8.5"x11", 11"x17", 12"x18", 13"x19"
Paper Feeder Capacity	200 Sheets
Trimming Methods	Flush Cut or Border Cut
Operation Panel	Color LCD Display
Power Supply	100-240 VAC, 50-60Hz
Dimensions (LxWxH)	48" x 23.5" x 44"
Weight	Laminator: 163 lbs